

2/PRTS

09/646986

529 PCT/PTO 26 SEP 2000
PCT/EP99/01729

WO 99/49973

MINIATURIZED MICROTITER PLATE FOR HIGH THROUGHPUT
SCREENING

5 The invention relates to a miniaturized microtiter plate for HT screening (high throughput screening).

10 In this screening it is desirable to minimize the consumption of assay components and of the substances from the screening libraries and to maximize the throughput of screening assays. This can be achieved by miniaturizing screening assays. However, it is necessary in this case to charge appropriate microtiter plates having an assay volume of about 0.5 to 10 μ l, preferably 1 to 6 μ l, particularly preferably 1 to 2 μ l. The only ones available to date are a few prototypes which can be processed only by particular analyzers. However, there is a need for microtiter plates which permit analysis with very sensitive detectors (with confocal optics) and allow charging with "nanodispensers". A further desirable feature is prevention of evaporation.

20 Microtiter plates have been disclosed by Greiner, 64943 Hirschberg, (Micro-Assay Plate, 1536 wells). In this case, the effective volume of the sample carriers is relatively large (4-8 μ l) and they do not permit "single molecule detection". Although the effective volume of the Corning Costar microtiter plates (Corning Costar Deutschland, 55924 Bodenheim) is between 1 and 2 μ l, the frame of the microtiter plates is too thin so that conventional robotic systems are unable to transport the microtiter plates. "Single molecule detection" is impossible in this case, too. A Hellma brochure (1994) "Silica Glass Microassay Plates" discloses microassay plates with a base made of silica glass and 384 wells with a diameter of 3.5 mm. However, besides the large assay volume, these microassay plates have frames which are insufficiently broad and bases which are too thick (> 1 mm) to allow analysis using confocal optics. US 5,487,872 describes multiassay microtiter plates for UV spectroscopy having glass plates with a minimum thickness of 0.38 mm. These microtiter plates are also unsuitable for analysis using confocal optics. Microassay plates with lids to prevent evaporation are described in a Radleys brochure (1997) "Specialist Micro Titer Plates & Accessories".

The object of the invention is to provide a remedy for this.

This takes place according to the invention by a miniaturized microtiter plate which has a body made of plastic and a base made of glass and has 1000 to 4000 vessels (wells), preferably 1400 to 2500 vessels (wells), particularly preferably 1536 vessels (wells), the diameter of the vessels (wells) is approximately 1.0 to 1.8 mm, preferably 1.2 to 1.5 mm, the base of the microtiter plate has a thickness of 0.07 to 0.2 mm, preferably 0.12 to 0.17 mm, particularly preferably 0.15 mm, the distance between the center of the outer vessels (wells) and the edge of the glass base is 4 to 11 mm, preferably \geq (greater than/equal to) 5.5 mm and the microtiter plate has a lid to prevent evaporation.

The miniaturized microtiter plate usually has a size of 10.0-15.0 x 7.0-10.0 cm, preferably 12.7 x 8.5 cm. However, sizes differing from this are also possible.

The shape of the vessels (wells) is variable. Thus, for example, vessels which are round, have corners or have rounded corners can be used. Round vessels are preferred. It is likewise possible for the number of vessels (wells) to differ from the abovementioned values. The angle between base and wall of the wells can vary between 20° and 90°.

It is important to use the correct material to produce microtiter plates. The body of the microtiter plate consists of plastic such as, for example, polystyrene, polypropylene, polycarbonate, Vectra®, Hostalen®, Topas®. The microtiter plates are usually produced by injection molding (or embossing). The plastic cools after the injection molding. Warping of the microtiter plate is possible during this (because of local differences in the rate of cooling). It is thus beneficial to use a material which produces only a very slight "curvature".

The lid of the microtiter plate is likewise made of plastic and sits form-fittingly on the microtiter plate. The thickness of the base (material: glass) of the microtiter plate (0.07 - 0.20 mm) and the diameter of the vessels (about 1.0 - 1.8 mm), and the distance between the center of the outer vessels (wells) and the edge of the glass base, which is 4 to 11 mm, allow analysis of the microtiter plate using confocal optics. The use of confocal optics has the following advantages:

1. The sensitivity is very high (compared with non-confocal optics) since even individual molecules can be detected in some circumstances (single molecule detection)

2. Because the sensitivity is high, the measurement time can be less and thus the overall rate of analysis of a microtiter plate can be increased (compared with many non-confocal optics).

3. Since the focus of confocal optics is very small (usually distinctly less than 10 μm), detection of background signals is greatly reduced and thus the signal/noise ratio is better (compared with non-confocal optics).

The base, which consists of glass, of the microtiter plate can be coated with various chemical and biological substances, such as, for example, cellulose, cellulose derivatives, dextrans, polyethylene glycols, in order to suppress nonspecific binding. It ought likewise to be possible for the base to carry biological molecules which specifically bind other substances. The latter is important for use in drug screening, for example for sandwich assays.

Possible embodiments of the microtiter plate according to the invention are described in detail below with reference to Figures 1 to 3. The invention is, however, not restricted to these embodiments.

Fig. 1: Perspective depiction of the microtiter plate with lid lifted off

Fig. 2: Section along plane II-II from Fig. 1

Fig. 3: Section along plane III-III from Fig. 1

Fig. 1 shows a perspective depiction of the microtiter plate with vessels (3). The frame (1) has a length of $a = 127 \text{ mm}$ and a width of $b = 85 \text{ mm}$. The lid (4) with projections (5) is shown in the lifted-off state.

Fig. 2 depicts a section along plane II-II. The glass base (2) is fastened underneath the microtiter plate. The edge distance (a1) is 3 - 8 mm, preferably 6 mm, and the distance (a2) is 6 - 11 mm, preferably 9.5 mm. The corresponding edge distance (b1) in Fig. 3 is likewise 3 - 8 mm, preferably 6 mm, and the distance (b2) is 4 - 11 mm, preferably 6.5 mm. The distances between the center of the outer vessels (wells) and the edge of the glass base (a3, b3) are 4 - 11 mm. The height of the frame of the microtiter plate is (c) = 6 - 20 mm, preferably 6 - 15 mm, particularly preferably 6 mm, and the inner height (c1) is 3 - 12 mm, preferably 3 mm. The vessel diameter (d) is between 1.0 and 1.8 mm, particularly preferably

項目	単位	備考
1. 学費	100,000	
2. 授業料	100,000	
3. 教材費	100,000	
4. 実験費	100,000	
5. 図書費	100,000	
6. 雑費	100,000	
7. 奨学金	100,000	
8. 学食費	100,000	
9. 寮費	100,000	
10. 交通費	100,000	
11. 保険料	100,000	
12. 医療費	100,000	
13. 生活費	100,000	
14. 雑費	100,000	
15. 雑費	100,000	
16. 雑費	100,000	
17. 雑費	100,000	
18. 雑費	100,000	
19. 雑費	100,000	
20. 雑費	100,000	
21. 雑費	100,000	
22. 雑費	100,000	
23. 雑費	100,000	
24. 雑費	100,000	
25. 雑費	100,000	
26. 雑費	100,000	
27. 雑費	100,000	
28. 雑費	100,000	
29. 雑費	100,000	
30. 雑費	100,000	
31. 雑費	100,000	
32. 雑費	100,000	
33. 雑費	100,000	
34. 雑費	100,000	
35. 雑費	100,000	
36. 雑費	100,000	
37. 雑費	100,000	
38. 雑費	100,000	
39. 雑費	100,000	
40. 雑費	100,000	
41. 雑費	100,000	
42. 雑費	100,000	
43. 雑費	100,000	
44. 雑費	100,000	
45. 雑費	100,000	
46. 雑費	100,000	
47. 雑費	100,000	
48. 雑費	100,000	
49. 雑費	100,000	
50. 雑費	100,000	
51. 雑費	100,000	
52. 雑費	100,000	
53. 雑費	100,000	
54. 雑費	100,000	
55. 雑費	100,000	
56. 雑費	100,000	
57. 雑費	100,000	
58. 雑費	100,000	
59. 雑費	100,000	
60. 雑費	100,000	
61. 雑費	100,000	
62. 雑費	100,000	
63. 雑費	100,000	
64. 雑費	100,000	
65. 雑費	100,000	
66. 雑費	100,000	
67. 雑費	100,000	
68. 雑費	100,000	
69. 雑費	100,000	
70. 雑費	100,000	
71. 雑費	100,000	
72. 雑費	100,000	
73. 雑費	100,000	
74. 雑費	100,000	
75. 雑費	100,000	
76. 雑費	100,000	
77. 雑費	100,000	
78. 雑費	100,000	
79. 雑費	100,000	
80. 雑費	100,000	
81. 雑費	100,000	
82. 雑費	100,000	
83. 雑費	100,000	
84. 雑費	100,000	
85. 雑費	100,000	
86. 雑費	100,000	
87. 雑費	100,000	
88. 雑費	100,000	
89. 雑費	100,000	
90. 雑費	100,000	
91. 雑費	100,000	
92. 雑費	100,000	
93. 雑費	100,000	
94. 雑費	100,000	
95. 雑費	100,000	
96. 雑費	100,000	
97. 雑費	100,000	
98. 雑費	100,000	
99. 雑費	100,000	
100. 雑費	100,000	